

SMART-JET MAX

BLUETOOTH TIJ INK JET PRINTER

Bluetooth Technology, 1" tall seamless print area and bulk inks for complete coding control.

With a 1" tall seamless print area that doesn't have to be stitched together, MSSC Smart-Jet Max Inkjet Printers are compact, reliable and can be controlled wirelessly via bluetooth technology (no router needed). This innovative coder can print bar codes, QR codes and logos on porous and non-porous surfaces using bulk inks. A large display screen makes it easy to read and simple to operate.



Contact your distributor to order or to see the full line of superior quality MSSC products.



Phone: (618) 343.1006 Fax: (618) 343.1016
926 McDonough Lake Road, Collinsville, Illinois 62234 USA

WWW.MSSCLLC.COM

SMART-JET MAX

BLUETOOTH TIJ INK JET PRINTER

Features:

- One to eight lines of print (25.4mm to 2.54mm)
- Large, color screen rotates with printer
- Smart phone connectivity with Smart-Jet Max software and app
- Control printer via Bluetooth with smart phones and tablets using Android operating systems for real time reporting
- Prints on porous, semi-porous and non-porous surfaces
- No moving parts and maintenance-free
- Up to 150 High-resolution characters per line
- Plug and print with Thermal Inkjet Technology
- Prints text, logos, barcodes, counter, shift codes, box/lot, date, time and expiry date
- Anti-shock mounting mechanism adjusts to irregularities in box for consistently smooth and high-quality printing results
- Static bar codes
- Stand alone operation with wireless keyboard
- Store up to 100 messages on printer's memory
- Password protected
- Back up and restore to USB
- Multiple operating languages
- 4 print directions
- Solvent and porous 40mL cartridges and 400mL bulk inks available
- Internal photocell integrated



Pieces included in package

Specifications:


- **Dimensions:** (L x W x H): 4.23 x 2.93 x 3.26 (in) or 107.5 x 74.5 x 83 (mm)
- **Light Weight:** 1 lb. 2.5 oz (526.6g) excluding cartridge
- **Display:** Automatic rotation 2.8" 256K colors TFT LCD display
- **Power Supply:** 12VDC – 5A, 60W
- **Throw Distance:** Up to 0.25 in (6 mm)
- **Operating Temperature Range:** between 41° F to 122° F (5° C to 50° C)
- External photocell, alarm beacon, and/or encoder available



Slim Print Head



App works on Android devices



Porous and non-porous print